



Lighting Specs

Control, Dimming, and Color

- (1) Express 48/96 Control console
- (1) 48 channel sensor Touring rack w/ soco and pin outs
- (1) Fleenor opto splitter 5 pin in x 5-5 pin out
- (12) HES color Merge Dichroic color mix
- (1) HES color PSU Power supply

Instruments

[All lights have C clamps, lamp, safety chain and 2P&G connector (except spots, Edison connector)]

- (2) Lycian M2 1200 med. Spotlights 1200w
- (4) ETC Source 4 5 degree 750w
- (10) ETC Source 4 10 degree 750w
- (4) ETC Source 4 19 degree 575w
- (4) ETC Source 4 26 degree 575w
- (4) ETC Source 4 36 degree 575w
- (30) ETC Source 4 par 575w
- (12) Altman 3-cell cyc w/ passthru 1000w
- (6) TMB floor base
- (4) Ushio lamp 750w
- (8) Ushio lamp 575w

Cable

- | | |
|--------------------------------------|--|
| • (3) TMB adapter 5 pin M to 3 pin F | • (1) TMB 12/14 multi 90' |
| • (2) TMB 5 pin DMX 10' | • (2) TMB 12/14 multi 100' |
| • (1) TMB 5 pin DMX 150' | • (1) TMB 12/14 multi 105' |
| • (1) TMB 5 pin DMX 200' | • (1) TMB 12/14 multi 110' |
| • (1) TMB 5 pin DMX 300' | • (2) TMB 12/14 multi 115' |
| • (10) TMB 4 pin scroller 10' | • (1) TMB 12/14 multi 120' |
| • (1) TMB 4 pin scroller 200' | • (2) TMB 12/14 multi 125' |
| • (1) TMB 4 pin scroller 300' | • (1) TMB 12/14 multi 130' |
| • (30) TMB stage pin 2-fer | • (1) TMB 12/14 multi 140' |
| • (10) TMB stage pin 3-fer | • (1) TMB 12/14 multi 150' F not attached |
| • (10) TMB stage pin | • (2) TMB 12/14 multi 200' |
| • (10) TMB stage pin | • (2) TMB 12/14 multi 300' |
| • (10) TMB stage pin | • (9) 2 P&G fanout 6' all circuits |
| • (10) TMB stage pin | • (1) 2 P&G fanout 3,6,9,12,18' circuits 1-6 |
| • (1) 5 wire 4/0 camlok 25' | • (9) 2 P&G fanout 2,4,6,8,10,12' circuits 1-6 |
| • (1) TMB 12/14 multi 75' | • (3) 2 P&G fanout 3' all circuit |
| • (1) TMB 12/14 multi 85' | |